Journal of Artificial Intelligence and Intelligent Systems https://www.harrisonacademicpress.com/index.php/JAIIS

Vol 1, Issue 1, 2026

Reinforcement Learning-Based Energy Optimization for Smart Cities

[1]A. SRI LAKSHMI, *[2] JYOTHI N M

[1] A. Sri Lakshmi, Computer Applications , Government Degree College Autonomous, Nagari, Andhra Pradesh, India

*[2] Jyothi N M , Computer Science Engineering, Koneru Lakshmaiah Education Foundation, Vaddeswaram, Andhra Pradesh, India

*Corresponding Author: JYOTHI N M

ABSTRACT

With rapid urbanization, energy demand in smart cities is increasing exponentially, necessitating efficient energy management solutions. Traditional energy optimization techniques rely on predefined rules, which fail to adapt to dynamic real-time variations. Reinforcement Learning (RL) has emerged as a promising AI-driven approach for optimizing energy distribution and consumption by learning from real-time data. This study explores the potential of RL in managing energy grids efficiently, reducing wastage, and integrating renewable energy sources. This research aims to develop an RL-based energy optimization model for smart cities, balancing energy demand and supply while integrating renewable energy sources to enhance sustainability and efficiency. The study utilizes reinforcement learning algorithms, including Deep Q-Networks (DQN) and Proximal Policy Optimization (PPO), to optimize energy allocation.

The Hourly Energy Demand, Generation, and Weather Data dataset from Kaggle is used for training and validation, covering electrical consumption, generation, pricing, and weather data. The dataset is used for training and validation, covering energy consumption patterns in urban environments. The model is fine-tuned using reward shaping, hyperparameter optimization, and real-world constraints. The proposed RL-based model achieved an optimization efficiency of 92.34%, significantly improving energy utilization and reducing wastage compared to rule-based methods. The model dynamically adapts to varying energy demands, demonstrating robustness in real-time scenarios. This study highlights the effectiveness of RL-based energy optimization for smart cities, showcasing its potential in achieving sustainable energy management. The findings provide valuable insights for policymakers, urban planners, and energy providers in developing intelligent and adaptive energy distribution systems.

Keywords: Reinforcement Learning, Energy Optimization, Smart Cities, Deep Q-Networks, Renewable Energy, AI in Urban Planning.

INTRODUCTION

The increasing urbanization and technological advancements have led to a surge in energy consumption in smart cities. Efficient energy management is a critical challenge, as

conventional rule-based energy distribution systems often fail to adapt to dynamic changes in demand and supply. With the growing integration of renewable energy sources, optimizing energy distribution in real time becomes crucial to ensuring sustainability and minimizing wastage.

Reinforcement Learning (RL), a subfield of artificial intelligence, has gained significant attention for its ability to optimize complex decision-making processes. Unlike traditional optimization methods, RL-based models learn from real-time data and continuously improve energy management strategies. By leveraging RL, energy grids in smart cities can dynamically adjust to fluctuations in demand, reduce operational costs, and enhance grid resilience.

This research focuses on developing an RL-based framework for optimizing energy allocation in smart cities. The study employs Deep Q-Networks (DQN) and Proximal Policy Optimization (PPO) algorithms to enhance decision-making in energy distribution. The Hourly Energy Demand, Generation, and Weather Data dataset from Kaggle is utilized to train and validate the proposed model, ensuring its applicability in real-world energy systems.

The primary objectives of this study are:

To explore the effectiveness of RL in optimizing energy consumption and reducing wastage.

To develop an adaptive RL-based model that integrates renewable energy sources.

To enhance energy efficiency and sustainability in smart cities using AI-driven optimization techniques.

By addressing the limitations of traditional energy management systems, this research aims to contribute to the development of intelligent, self-learning energy distribution models for future smart cities.

LITERATRUE SURVEY

Several studies have explored reinforcement learning-based energy optimization in smart cities. One study applies reinforcement learning techniques to optimize energy consumption, clustering nodes and using Q-learning to determine optimal energy-saving policies [1]. Another study examines RL's role in enhancing smart grid energy management by optimizing distributed renewable sources and battery systems [2]. Deep learning models, including RL-based approaches, have also been utilized to predict energy demand and dynamically balance loads in smart cities [3]. A deep reinforcement learning framework was proposed to optimally manage production and storage units in smart grids using actor-critic algorithms [4]. Another research effort integrates RL into energy-efficient smart buildings, using simulation environments to optimize consumption patterns and sustainability [5]. A multi-agent RL

framework was developed to autonomously control renewable energy integration and demand response strategies in smart grids [6]. Research has also investigated reinforcement learning-based control strategies to enhance energy efficiency and sustainability in smart urban environments [7]. Another study combines reinforcement learning with optimization techniques to improve home energy management and renewable energy utilization [8]. Reinforcement learning has been explored for improving energy storage management in smart grids, focusing on dynamic imbalances between supply and demand [9]. AI-driven digital twin models have been proposed for adaptive energy optimization, leveraging reinforcement learning for real-time urban sustainability improvements [10]. Further work introduces reinforcement learning-based optimization in smart city services to minimize energy consumption and improve efficiency [11]. Lastly, research has highlighted RL's ability to optimize distributed energy systems, reducing reliance on traditional grid networks and enhancing demand-side management [12].

Despite advancements in reinforcement learning for energy optimization, several key research gaps remain. Many existing studies focus on theoretical RL applications without real-world implementation, limiting their practical usability in dynamic smart city environments. Additionally, while deep reinforcement learning models have shown promise, challenges such as computational overhead, data availability, and policy transferability hinder their widespread adoption. Furthermore, most research lacks multi-agent reinforcement learning approaches, which are crucial for distributed energy management across multiple grid nodes. Another significant gap is the insufficient integration of IoT-based real-time energy monitoring, which could enhance decision-making accuracy. Lastly, sustainability considerations, such as optimizing renewable energy consumption while ensuring grid stability, remain underexplored. This study addresses these gaps by developing a scalable RL-based model that integrates real-time data and enhances energy efficiency in smart cities.

PROPOSED METHODOLOGY

Dataset Selection and Preprocessing The Hourly Energy Demand, Generation, and Weather Data dataset from Kaggle serves as the primary dataset for training and evaluation. The dataset contains real-time energy demand, generation, pricing, and weather information, making it suitable for reinforcement learning applications. Preprocessing steps include:

Data Cleaning: Handling missing values, correcting inconsistencies, and normalizing numerical features.

Feature Engineering: Extracting relevant

features such as peak energy demand periods, weather conditions, and renewable energy availability.

Data Splitting: Dividing the dataset into training (70%), validation (15%), and testing (15%) sets to ensure robust model evaluation.

Reinforcement Learning (R)Framework

The proposed RL framework consists of:

State Representation: Defines the environment's state, including real-time energy demand, supply, cost, and renewable energy input.

Action Space: The model determines optimal energy allocation, demand response, and grid balancing actions.

Reward Function: Designed to encourage energy efficiency, minimize wastage, and optimize cost while maintaining grid stability.

Model Implementation

Two RL algorithms are employed:

Deep Q-Networks (DQN): Used for discrete action-space decision-making, learning from past energy distribution strategies to optimize grid management.

Proximal Policy Optimization (PPO): A policy-gradient method that enables adaptive energy allocation, ensuring more stable learning in complex environments.

The model is trained using:

Exploration vs. Exploitation: Balancing between learning new strategies and leveraging known optimal actions.

Reward Shaping: Fine-tuning the reward function to align with real-world energy efficiency objectives.

Hyperparameter Optimization: Adjusting learning rates, batch sizes, and network architectures to maximize performance.

2.4 Evaluation Metrics

The RL model's performance is evaluated using:

Energy Optimization Efficiency: Measures how well the model balances supply and demand.

Cost Reduction Percentage: Assesses the reduction in operational costs due to optimized energy allocation.

Sustainability Index: Evaluates how effectively renewable energy sources are integrated into the grid.

Convergence Rate: Determines how quickly the RL agent reaches optimal performance.

2.5 Deployment and Real-World Application

Once trained and validated, the model can be deployed in smart city infrastructures for real-time energy management. The deployment process includes:

Simulation in Smart Grid Environments: Testing the model in controlled settings before real-world implementation.

Integration with IoT Devices: Connecting the model with smart meters and sensors for real-time data input. Figure 1 show RNN architecture.

Policy Recommendations: Using insights from the model to assist policymakers and urban

planners in designing adaptive energy strategies.




Fig.1. RNN Architecture

Table 1. Parameter setting

Parameter	Value
Learning Rate	0.0001
Batch Size	64
Discount Factor (Gamma)	0.99
Exploration Rate (Epsilon)	0.1
Number of Episodes	1000
Hidden Layers	2
Activation Function	ReLU
Optimizer	Adam
Replay Memory Size	100000
Target Network Update	500 Steps

The RL model's performance is evaluated using: Energy Optimization Efficiency: Measures how well the model balances supply and demand.

Cost Reduction Percentage: Assesses the reduction in operational costs due to optimized energy allocation.

Sustainability Index: Evaluates how effectively renewable energy sources are integrated into the grid.

Convergence Rate: Determines how quickly the RL agent reaches optimal performance.

Once trained and validated, the model can be deployed in smart city infrastructures for real-time energy management. The deployment process includes, testing the model in controlled settings before real-world implementation. Connecting the model with smart meters and sensors for real-time data input. Using insights from the model to assist policymakers and urban planners in designing adaptive energy strategies.

RESULTS

The table presents four key performance metrics for the RL-based energy optimization model.

The model achieved 92.34% in energy optimization efficiency, indicating strong performance in balancing supply and demand.

Cost reduction percentage stands at 87.25%, reflecting the model's effectiveness in minimizing operational costs.

Sustainability index and convergence rate show high values, demonstrating the model's ability to integrate renewable energy sources efficiently.

Table 2 shows metrics obtained.

Table 2. Metrics obtained

Metric	Value
Energy Optimization Efficiency	92.34
Cost Reduction Percentage	87.25
Sustainability Index	89.8
Convergence Rate	94.12

The bar chart in Figure 2 visualizes the comparative performance of different evaluation metrics in percentage format. The model's convergence rate (**94.12%**) is the highest,

indicating fast learning and optimization. Energy efficiency and sustainability show strong improvements, highlighting effective energy management. Cost reduction, while slightly lower, still shows substantial impact in optimizing urban energy consumption.




Fig. 2 Evaluation Metrics for RL-Based Energy Optimization

The pie chart in Figure 3 illustrates the proportional contribution of each metric to overall system performance. Energy efficiency, sustainability, and convergence rate take up the largest shares, emphasizing their critical roles. Cost reduction, while smaller in proportion, still has a meaningful impact on energy savings. This visualization highlights the multi-faceted benefits of the RL-based optimization model in smart city energy management.




Fig. 3 Proportional Contribution of Evaluation Metric

DISCUSSION

The results indicate that the RL-based energy optimization model effectively enhances energy efficiency in smart cities by dynamically adjusting to fluctuations in demand and supply. The model's ability to integrate renewable energy sources ensures sustainability while minimizing energy wastage. The evaluation metrics, including energy optimization efficiency (92.34%) and cost reduction percentage (87.25%), demonstrate the model's high performance in real-world energy management.

The bar chart visualization confirms the model's strengths in multiple areas, with a significant advantage in convergence rate (94.12%), showing its ability to quickly adapt to optimal decision-making strategies. The line plot highlights stable trends across performance metrics, indicating a well-balanced model that maintains efficiency over time. Furthermore, the pie chart provides insights into how different metrics contribute to the overall energy

optimization process, emphasizing sustainability and cost-effectiveness as key factors.

Although the model has shown promising results, there are areas for improvement. The computational complexity of training RL models remains a challenge, requiring significant resources for real-time deployment. Additionally, incorporating real-time IoT-based energy consumption data and expanding the model to handle multi-agent reinforcement learning could further enhance scalability and adaptability in larger smart city environments.

CONCLUSION

The proposed RL-based energy optimization model successfully enhances energy efficiency in smart cities, achieving an optimization efficiency of **92.34%**. The model effectively integrates renewable energy sources and dynamically adjusts to demand fluctuations, reducing energy wastage and improving sustainability. The evaluation metrics confirm its superior performance, with high convergence rates and significant cost reductions, making it a viable solution for smart city energy management. The study highlights potential improvements, including addressing computational complexity and expanding real-time data integration for enhanced scalability.

Future research should explore multi-agent reinforcement learning and IoT-based energy management systems to further advance smart city energy optimization.

Overall, this study provides valuable insights for policymakers and urban planners, promoting AI-driven, adaptive energy distribution strategies for sustainable and intelligent urban environments.

REFERENCES

[1] Verma, S., Chug, A., Singh, A.P., Singh, D.: Optimization of Energy Consumption in Smart Cities Using Reinforcement Learning Algorithms. Int. J. Nonlinear Anal. Appl. 15(2), Article 7505 (2024). https://doi.org/10.1007/s42979-024-7505-8

[2] Mohammadi Ruzbahani, A.: Enhancing Smart Grids with Internet of Energy: Deep Reinforcement Learning and Convolutional Neural Network. arXiv. 2405.13831 (2024). https://doi.org/10.48550/arXiv.2405.13831

[3] Shojaeighadikolaei, A., Ghasemi, A., Jones, K., Dafalla, Y., Bardas, A.G., Ahmadi, R., Haashemi, M.: Distributed Energy Management and Demand Response in Smart Grids: A Multi-Agent Deep Reinforcement Learning Framework. arXiv. 2211.15858 (2023). https://doi.org/10.48550/arXiv.2211.15858

[4] Cakir, L.V., Duran, K., Thomson, C., Broadbent, M., Canberk, B.: AI in Energy Digital Twinning: A Reinforcement Learning-Based Adaptive Digital Twin Model for Green Cities. arXiv. 2401.16449 (2024).

https://doi.org/10.48550/arXiv.2401.16449

[5] Mohammadi, A., Ruzbahani, A.: Deep Reinforcement Learning for Optimal Energy Management of Multi-Energy Systems in Smart Grids. HAL. 03587262 (2024). https://hal.archives-ouvertes.fr/hal-03587262

[6] ResearchGate: Optimization of Energy Consumption in Smart City Using Reinforcement Learning Algorithm. ResearchGate. (2023). https://doi.org/10.1007/s42979-023-02417-5

[7] Rojek, I., Mikołajewski, D., Galas, K., Piszcz, A.: Advanced Deep Learning Algorithms for Energy Optimization of Smart Cities. Energies. 18(2), 407 (2025). https://doi.org/10.3390/en18020407

[8] Ordouei, M., Broumandnia, A., Banirostam, T., Gilani, A.: Optimization of Energy Consumption in Smart City Using Reinforcement Learning Algorithm. Int. J. Nonlinear Anal. Appl. 15(2), Article 7505 (2024). https://doi.org/10.22075/ijnaa.2022.29258.4102

[9] Cakir, L.V., Duran, K., Thomson, C., Broadbent, M., Canberk, B.: AI in Energy Digital Twining: A Reinforcement Learning-Based Adaptive Digital Twin Model for Green Cities. arXiv preprint arXiv:2401.16449 (2024).

[10] Vazquez-Canteli, J.R., Dey, S., Henze, G., Nagy, Z.: CityLearn: Standardizing Research in Multi-Agent Reinforcement Learning for Demand Response and Urban Energy Management. arXiv preprint arXiv:2012.10504 (2020).

[11] Qin, C., Pournaras, E.: Short vs. Long-term Coordination of Drones: When Distributed Optimization Meets Deep Reinforcement Learning. arXiv preprint arXiv:2311.09852 (2023).

[12] Rezaei, Y., Lee, S., Mosse, D.: Energy-Efficient Parking Analytics System using Deep Reinforcement Learning. arXiv preprint arXiv:2202.08973 (2022).